

1080P Webcam

UAI4J1703C

1080P USB Camera, built-in microphones, up to 6 meters omnidirectional voice pickup, support USB, plug and play, provide high quality A/V experiences.



1080P



Microphone Array



Dual Stream



Privacy Masking



Plug and Play



Features

1080P + 90° Wide-angle Lens

Support 1080p HD, support 1080@30FPS/25FPS image encoding output, and compatible with 720P resolution. With a 90 ° ultra-wide-angle lens. Two lenses are available, 90 °/ 90 ° (with AF).

USB 2.0

Full function USB 2.0 interface, power supply, video, audio.

Audio

The built-in microphone array can be omnidirectional. The distance of the pickup is as high as 6 meters. Unique noise suppression and AGC algorithm make your voice perfect.

ePTZ

No mechanical rotating device for more reliable and robust noise-free PTZ feature with more accurate rotation.

Privacy Masking

Equipped with an integrated sliding privacy cover to ensure the privacy.

Low Illumination

The new generation high performance CMOS image sensor can significantly reduce the image noise in low illumination. With the 2D and 3D noise reduction algorithms, even in an ultra-low illumination environment, camera can still deliver a sharp and clean image with more than 55dB S/N ratio.

Dual-streaming

Support dual-streaming simultaneously (YUY2, MJPEG and H.264).

Easy Installation

The standard configuration includes a damped rotary support, which is compatible with almost 100% of the displays available on market; it's easy to install, stable and reliable.

Product Specification

Camera Spec

Sensor	1/2.8 inches, CMOS, Effective Pixels:2.07 Megapixe Scanning
Mode	Progressive
Type of Lens Mount	M12
Lens	f=2.8mm, Horizontal FOV: 90°
Minimum Illumination	0.5Lux @ (F1.8, AGC ON)
Shutter	1/30s ~ 1/10000s
White Balance	Auto, Manual, VAR
Bracket	Damping rotating bracket
Digital Noise Reduction	2D&3D Digital Noise Reduction
Backlight Compensation Support	
Digital Zoom	4x

USB Spec

Operating System	Windows® 7 (only supports 1080P and below), Windows 8.1, Windows 10 or higher; MacOS™ 10.10 or higher; Linux (need to support UVC);
Hardware Requirements	2.4 GHz Intel® Core 2 Duo Processor or higher 2 GB memory or higher USB 2.0
Color System / Compression	YUY2 / H.264 / MJPEG 1080P30/25;
Video Format	720P30/25; 960x540P30/25; 640x360P30/25;
USB Video Communication Protocol	UVC 1.1
UAC	Support
UVC PTZ Control	Support (ePTZ)

I/O


USB Interface	1 x USB 2.0, type A
---------------	---------------------

Generic Spec

Input Voltage	5V (USB Power Supply)
Input Current	0.2A (Max.)
Operating Temperature	0°C ~ 40°C
Storage Temperature	-40°C ~ 60°C
Power Consumption	1W (Max.)
Dimension	103mm (W) × 27mm (D) × 30mm (H)
Net Weight	153g



Interface Diagram



1 — USB